

REFORAC 900

TECHNICAL DATA SHEET

1. PRODUCT DESCRIPTION & USES:

Reforac Silicone 900 is a one part, very low modulus, neutral system sealant that cures with atmospheric moisture producing a flexible rubber which is extremely resistant. It does not contain corrosive or strong smelling additives. This neutral sealant is oxim-free.

Reforac Silicone 900 preserves all properties of elasticity and adherence with no ageing problems, emaining stable to atmospheric agents. Reforac Silicone 900 is a high quality sealant and has excellent adherence to most substrates used in construction.

SPECIFICALLY RECOMMENDED FOR:

- Sealing of expansion joints
- Concrete to concrete joints sealing
- Sealing of light facades
- Water-tight joints sealing between concrete ad structural carpentry
- Window sealing
- All applications where odourless mastic is needed

2. GENERAL DATA & CHEMICAL PROPERTIES:

THE MAIN CHARACTERISTICS BEFORE CURING ARE THE FOLLOWING

Aspect	Thixotropic paste
Specific Gravity	1.16 g/cm ³
Skinning Time	12-20 min
Tack Free Time	45-50 min
Application Temperature	+5°C to +40°C

AFTER CURING

Service Temperature	-40°C to +120°C
---------------------	-----------------

MECHANICAL CHARACTERISTICS ARE THE FOLLOWING

Hardness Shore A	DIN 53505	12
Modulus 100%	ISO 8339	0.12 MPa
Tensile Strength	ISO 8339	0.25 MPa
Elongation at Break	ISO 8339	300 %

Reforac Silicone 900 complies with the requirements of the norm ISO 11600 type F 25 LM

APPLICATION:

- Surfaces to be sealed should be clean and dry, free of dust or grease, which could cause a deficient adherence.
- Cleaning of the surfaces should be done with suitable products in each case and following instructions and recommendations of the manufacturer.
- If unusual supports are used, it is recommended that some tests are carried out in case a primer is needed.
- Joints made with Reforac Silicone Sealant 900 should not be painted.

PACKAGING:

- Supplied in 310ml cartridge or 600 ml sausages.

COLOURS:

- Grey
- White grey
- Concrete grey
- Basalt grey
- Antracit grey
- Warm white
- Brown
- Black
- Other colours available on request

SHELF-LIFE:

It has a shelf life of 12 months stored in a dry place at or below 25°C

Material Safety Data Sheet available on request.

SPECIALISTS IN COATINGS ADHESIVES SEALANTS AND TAPES

info@reforac.com

www.reforac.com

DISCLAIMER:

This information, based on our expertise and tests, is believed to be reliable and is given in good faith, but without warranty. We cannot accept liability for any damage, loss, accident, and patent infringement or for operations not under our direct control resulting from the use of this information. We recommend that purchasers carry out their own tests, to determine to their own satisfaction, the suitability of any product for their particular purpose. As this product is used outside of our control, we cannot accept liability for any loss or damage whatsoever.