

REFORAC

Ready for any challenge

REFORAC GENERAL CATALOGUE



SILICONE SEALANTS



REFORAC 660 UNIVERSAL SILICONE

is formulated to perform over a wide range of indoor and outdoor applications. Universal silicone can be used as a filling and bonding material for glass, carpentry, metal, tile, PVC and building elements.

Colours: Black / White / Clear / Grey / Brown / Beige

Packing: 310 ml. x 25 per box

REFORAC 600R HIGH TEMPERATURE SILICONE

is used for joining and sealing joints, seams and cracks in places where high heat resistance is required. Adheres very well to glass, enamel, tiles, glazed ceramics and smooth metals. Particularly suited for joining and sealing oven and microwave windows, edges around hot plates, heating ducts, flues, heat screens for the fireplace.

Colours: Red

Packing: 310 ml. x 25 per box

REFORAC 500N NEUTRAL SILICONE

is one component, easy applicable, Alcoxy based neutral silicone sealant. Neutral silicone can be used as a filling and bonding material for glass or glazed surface, paint wood, aluminium and other metals, stone, concrete, GRP, PVC and other plastics.

Colours: Black / White / Clear / Grey / Brown / Beige

Packing: 310 ml. x 25 per box

REFORAC 600AF

is one component, easy applicable, Acetoxy based silicone sealant. REFORAC Pro can be used as filling and bonding material for ceramic tile, window, aluminium, metal, bathrooms and kitchens.

Colours: Black / White / Clear / Grey / Brown

Packing: 310 ml. x 25 per box

REFORAC 600 UNIVERSAL SILICONE

is formulated to perform over a wide range of indoor and outdoor applications. Universal silicone can be used as a filling and bonding material for glass, carpentry, metal, tile, PVC and building elements.

Colours: Black / White / Clear / Grey / Brown / Beige

Packing: 280 ml. x 25 per box

REFORAC 600F SHOWER CABIN

is one component, easy applicable, Acetoxy based silicone sealant. REFORAC Shower Cabin can be used as a filling and bonding material for ceramic tile, window, aluminium, metal, bathrooms and kitchens.

Colours: White / Clear

Packing: 310 ml. x 25 per box

SILICONE SEALANTS



REFORAC 600 AQUARIUM SILICONE

has been specifically formulated for the fabrication of fresh and salt-water aquariums. The bonds are unaffected by continuous immersion in water and it is non-toxic to fish when fully cured.

Colours: Black / Grey

Packing: 300 ml. x 25 per box



REFORAC 550 MIRROR SILICONE

is a neutral curing, Alkoxy based 100% silicone sealant with outstanding adhesion that provides a permanent flexible bond for mirrors to painted surfaces, plaster, metal, or wood. It can be used for mirror bonding, PVC carpentry assembling, for high structures among cushions to stretch, for attaching glass into plastic and metal.

Colours: White

Packing: 310 ml. x 25 per box



REFORAC 400 SILICONE

is a one component, easy applicable, neutral silicone. It provides excellent adhesion for plastic, metal, wood joineries assemble to the glass for insulating glass applications, door and window joints, fixing mirrors, fixing PVC joineries.

Colours: Black / White / Clear / Grey

Packing: 280 ml. x 25 per box

ACRYLIC SEALANTS



REFORAC ACRYLIC SEALANT

can be used as a filling, insulating and imperviousness material for construction material, metal, wood, PVC, aluminium frames, wall cracks.

Colours: White / Black / Grey / Brown / Gold oak

Packing: 310 ml. x 25 per box

REFORAC SILICONIZED SEALANT

can be used as a filling, insulating and imperviousness material for construction material, metal, wood, PVC, aluminium frames, wall cracks. It provides maximum adhesion and flexibility.

Colours: White / Black / Grey / Brown / Gold oak

Packing: 310 ml. x 25 per box

REFORAC SUPER SILICONIZED SEALANT

is one component, water based filling mastic. It provides maximum adhesion and flexibility. REFORAC Super Siliconized Sealant can be used as a filling, insulating and imperviousness material for construction material, metal, wood, PVC, aluminium frames, wall cracks.

Colours: White / Black

Packing: 310 ml. x 25 per box



REFORAC EKO SEALANT

can be used as a filling, insulating and imperviousness material for construction material, metal, wood, PVC, aluminium frames, wall cracks.

Colours: White / Black / Grey / Brown / Gold oak

Packing: 310 ml. x 25 per box

ACRYLIC STRUCTURE

can be used to seal the joints, cracks, door and window frames, window sills, prefabricated materials, stairs, skirting, board, wood, sheet, chimneys, pipes and drains. Also it can be used for sealing wall cracks and adheres to brick, concrete, plasterwork, wood, glass, ceramic tiles, metals and rigid PVC.

Packing: 310 ml. x 25 per box

REFORAC PRO EXTERIOR

is an elastic water based acrylic for interior and exterior use with a very good adhesion to many materials, even on damp surfaces without using a primer. REFORAC Pro Exterior is rain resistant. It is suitable for sealing cracks, chinks, seams and connection joints that have a maximum 7,5% joint movement. Not suitable for joints exposed to continuous water immersion or joints which are totally closed used for sealing joints on buildings, assembling window and door frames as a filling and insulating material.

Colours: White / Black / Grey / Brown / Gold oak

Packing: 310 ml. x 25 per box

POLYURETHANE FOAMS

REFORAC B1 FIRE RESISTANT FOAM

is a one component isolation and construction polyurethane foam for industrial and building applications. The foam has an excellent dimension stability. The foam seals and fills joints, holes and gaps and cures in response to humidity. The use of the gun makes it easier to adjust the foam extrusion. Use the gun Reforac supplies. When cured the excess foam can be trimmed, sanded and painted. This foam can be applied on all building materials except silicone, Teflon, polyethylene and polypropylene.

It is resistant to practically most weather conditions, seawater, steam and moisture. Fire resistance up to 4 hours. Acts as a seal to prevent the passage of smoke and as an air-proof. Fills the large and small gaps and provides insulation. Can be used inside and outside (cured foam must be covered). Provides excellent adhesion to most construction materials. Can be applied to all kinds of building materials except silicone, Teflon, polyethylene and polypropylene. Do not apply on bitumen or other solvent sensitive surfaces.

Packing: 750 ml. x 12 per box (Gun Grade - Normal Grade)

REFORAC FLEXIBLE FOAM

is a one-component flexible gunfoam, an air humidity curing pre-polymerized mixture in an aerosol can. Flexible foam Foam is used for installation of doors and windows, insulation and fixation of tubes, filling holes and gaps, fixation of wall panels and roof stones, and for thermal insulation. (Especially for applications where higher joint movement is required). Cured foam is a good temperature and sound insulator, and has strong adhesive properties. Foam has high elasticity and shape recovery. IFT approved.

Packing: 750 ml. x 12 per box (Gun Grade)



POLYURETHANE FOAMS

REFORAC B3 PU-FOAM

is a one component isolation and construction polyurethane foam for industrial and building applications. The foam has an excellent dimension stability. The foam seals and fills joints, holes and gaps and cures in response to humidity. The use of the gun makes it easier to adjust the foam extrusion. Use the gun Reforac supplies. When cured the excess part can be trimmed, sanded and painted. This foam can be applied on all building materials except silicone, Teflon, polyethylene and polypropylene. It is resistant to practically most weather conditions, seawater, steam and moisture.

Packing: 750 ml. 845 gr. x 12 per box (Gun Grade - Normal Grade)

REFORAC ALL WEATHER FOAM -10/+35°C

is a one component isolation and construction polyurethane foam for industrial and building applications. The foam has an excellent dimension stability. The foam seals and fills joints, holes and gaps and cures in response to humidity. The use of the gun makes it easier to adjust the foam extrusion. Use the gun Reforac supplies. When cured the excess foam can be trimmed, sanded and painted. This foam can be applied on all building materials except silicone, Teflon, polyethylene and polypropylene. It is resistant to practically most weather conditions, seawater, steam and moisture.

Packing: 750 ml. 845 gr. x 12 per box (Gun Grade - Normal Grade)

REFORAC MEGA FOAM

is a one component isolation and construction polyurethane foam for industrial and building applications. The foam has an excellent dimension stability. The foam seals and fills joints, holes and gaps and cures in response to humidity. The use of the gun makes it easier to adjust the foam extrusion. Use the gun Reforac supplies. When cured the excess part can be trimmed, sanded and painted. This foam can be applied on all building materials except silicone, Teflon, polyethylene and polypropylene. It is resistant to practically most weather conditions, seawater, steam and moisture.

Packing: 875 ml. 1000 gr. x 12 per box (Gun Grade)

REFORAC FOAM CLEANER SPRAY

cleans foam residues and prevents choking up on top of the gun. More effective results can be achieved if it is applied immediately after usage.

Packing: 500 ml. 535 gr. x 12 per box

ADHESIVES, WATER BASED

REFORAC PANEL ADHESIVE

is a one component, high strength adhesive sealant. REFORAC Panel Adhesive can be used for sealing materials, such as strapor, heat isolation panels, wooden panels, wooden door and window frames, brooms, wainscoting, acoustic panels, ceramic faience and also it can be used for fittings and repairing.

Packing: 300 ml. x 25 per box

REFORAC LAMINATE AND PARQUET ADHESIVE

is a polyvinyl based and solvent free adhesive, especially suitable for pre-finished parquet (edge and heat), floor coverings, laminates, wooden furniture, etc. Particularly suitable if thermal stability and water resistance is required. Material alters the natural colour of wood. It can be used for lamination applications of laminate or natural parquet, furniture industry.

Colours: White (translucent after drying)

Packing: 500 gr. x 12 per box

REFORAC LIQUID NAIL SOLVENT FREE ADHESIVE

based on acrylic dispersions, which adheres to all common building surfaces and replaces nails and screws. It can be used for fix skirting boards in both wood and PVC, thresholds, panels, ceramic tiles and ornamental framework on to various substrates such as masonry, concrete, plaster, chipboard, plasterboard and wood. Also suitable for the adhesion of polystyrene foam and polystyrene tile.

Colours: White (translucent after drying)

Packing: 300 ml. x 25 per box



REFORAC MARBLE & STONE ADHESIVE

is an unsaturated polyester resin based, two component adhesive, which cures with a hardener. Material is easily applicable. Material's colour remains constant. Material does not diverge, crack, soften and bend between temperatures of -20°C to $+100^{\circ}\text{C}$ material doesn't have scent. Material is resistant to solvents, alkali and acid solutions. It can be used for bonding of marble, stone, ceramic wall tailings, clay, polishing stones, concrete and wood based materials.

Colours: Beige / White / Champagne

Packing: 250 gr. + Hardener 7 gr. x 24 per box
700 gr. + Hardener 21 gr. x 12 per box
1000 gr. + Hardener 30 gr. x 12 per box
1200 gr. + Hardener 35 gr. x 12 per box

ADHESIVES PU BASED

REFORAC PU 25

is a one-component, high-modulus polyurethane sealant that cures on exposure to atmospheric humidity. It is used in door, window and siding installation; in roofing systems to provide a weather-proof and expansion-proof seal on roof joints and exterior gaps; and, in concrete applications, to provide an abrasion as well as stress resistant seal parts that are exposed to heavy vehicle and pedestrian traffic. It possesses excellent adhesion to sheet iron, aluminium, stainless steel, lead, copper, ceramic, glass, wood and various plastic materials.

Colours: White / Black / Grey

Packing: 300 ml. x 25 per box aluminium cartridge
400 ml. x 25 per box sausage
600 ml. x 24 per box sausage

REFORAC PU 40

is a one-component, high-modulus polyurethane sealant that cures on exposure to atmospheric humidity. It possesses excellent adhesion to sheet iron, aluminium, stainless steel, lead, copper, ceramic, glass, wood and various plastic materials. It uses in sealing and bonding of ventilation ducts, gutters and spouts, body construction of cars, containers, caravans and in sealing of sheet metal seams.

Colours: White / Black / Grey

Packing: 300 ml. x 25 per box aluminium cartridge
400 ml. x 25 per box sausage
600 ml. x 24 per box sausage

REFORAC PU MARINE GRADE ADHESIVE

is one component, polyurethane based wood adhesive, which cures with moisture of air and has excellent resistance abilities to impact of water. It has a short drying time with gap filling ability by swelling with high adhesive capacity. Water resistant and applicable even to wet, wood made surfaces. It can be used for bonding of all kind of hard wood made materials. It can be used for installing of MDF, slab surfaces, Formica and doorframes, ships, yachts, furniture industry.

Packing: 700 gr. x 12 per box
500 gr. x12 per box
300 gr. x12 per box



OTHER ADHESIVES

REFORAC HYBRID 50 SHORE A

is ideal as an all-purpose industrial adhesive where speed of cure and high strength bonding are essential. This universal system will bond and seal nearly every kind of surface to almost every kind of substrate thus replacing mechanical fastening, can find use in a variety of industrial applications such as assembly, interior & exterior joint sealing as well as seam sealing of metal roofing and cover plates.

50 shore A exhibits good adhesive strength for typical industrial applications where diverse surfaces require bonding such as plastics to wood and plastics to metal. Primerless application allows faster operations and thus reduced processing costs. Surfaces must be clean, dry and free from contaminants that could hinder bonding. No primer needed.

Colours: White / Black / Clear / Beige / Grey

Packing: 290 ml. x 25 per box



OTHER ADHESIVES

REFORAC ONE COMPONENT PVC ADHESIVE

with stabilized synthetic resin and volatile solvent based. Easily applicable. Material should be mixed well before using. Approximate drying time is 10 minutes. It is used in joints of PVC pipes (water, gas) which are produced with or without pressure.

Colours: clear

Packing: R-12 50 gr. Tube x 48 per box
R-12 125 gr. Tube x 30 per box
R-12 250 gr. Can x 24 per box
R-12 500 gr. Can x 12 per box
R-12 1000 gr. Can x 12 per box

REFORAC 2C PROFESSIONAL RAPID ADHESIVE

is cyanoacrylate adhesive. When it is used together with spray the execution time for bonding is 15 seconds. It can be used for profile corner consist of MDF, to cover the cupboard, laminate.

Packing: 50 gr. cyanoacrylate + 200 ml. activator x 50 per box

- High performance
- Easy usage
- Rapid reaction
- Hardening in a short time
- Making strong anchorage for all materials like concrete, tile and walls

Packing: 380 ml. (A+B) x 12 per box

REFORAC HYBRID 35 SHORE A

is ideal as an all-purpose construction sealant. This universal sealant will bond and seal nearly every kind of surface to almost every kind of substrate. Due to its universal is suitable to replace the multitude of bonding systems previously required in construction applications, can find use in a variety of construction applications such as sealing perimeters, joint sealing and structural bonding. The speed of cure eliminates dirt pick-up whilst exhibiting high strength build-up displays good adhesive strength on typical construction substrates such as diverse plastics, concrete, wood and various metals. Surfaces must be clean, dry and free from contaminants that could hinder bonding. Primer not needed.

Colours: Clear

Packing: 290 ml. x 25 per box

REFORAC HD40

is a non- siliconized, lubricant effective, rust resolver, protective spray. It provides an oily surface, stops squeaks and prevents corrosion in vehicles, household appliances, hinges, springs. It creates a protective film layer in rusty areas, which are corroded. It avoids the oxidation in rusted bolts and nuts. It helps removing the moisture from the metal surfaces, electricity switches and car ignitions.

Colours: Clear / White / Black

Packing: 50 ml. x 48 per box

REFORAC RTV AUTO GASKET

is a fast curing, durable, flexible and low modulus Acetoxy based silicone sealant for use in special applications. It can be used as gasket for automobiles, differential cover, motor cover, carburettor cover and pumps, to seal in heating systems and thermostat.

Colours: Red / Blue / Black

Packing: 50 ml. x 48 per box

REFORAC TUBE ACRYLIC SEALANT

is one part flexible acrylic emulsion joint sealant with a high polymer proportion, providing an economic solution for low movement joints. Internal sealing around windows, doorframes skirting boards, covings and repairs to plaster work. Also applicable by installing wood, PVC and aluminium frames.

Colours: White

Packing: 100 gr. x 48 per box

YOU CAN FIND THE FOLLOWING PRODUCTS IN REFORAC SAUSAGE RANGE AS 400 ML. OR 600 ML

- REFORAC Silicone Sealant
- REFORAC Neutral Silicone Sealant
- REFORAC Super Arcylic Sealant
- REFORAC Siliconized Sealant
- REFORAC Super Siliconized Sealant
- REFORAC IGS (Insulating Glass Sealant)
- REFORAC SG (Structural Glazing Sealant)
- REFORAC Polyurethane Sealant
- REFORAC Pro

REFORAC

Ready for any challenge

FOR SAMPLES:

REFORAC BV
P.O. box 648
2100 AP Heemstede
The Netherlands

REFORAC

info@reforac.com
www.reforac.com

Average values are shown, unless otherwise specified. All tapes in our series need to be thoroughly tested on the surface of the specific application they are suited to. Reforac is not responsible for product damage, unless the entire test cycle was completed. Client decides on the suitability of the tapes for the intended application.